

Part No. **DCS-01/5**



Dry Contact Sensor

Sensor Features:

- Small, Lightweight Sensor
- Rugged Binding Posts
- Single Cable for Output Signals

Sensor Description:

The dry contact sensor provides a low voltage across a contact for the purpose of determining the state of the contact, 0 Volts = open and 5 Volts = closed. It provides a way of monitoring a contact that has no applied voltage. It is not for use on live circuits. The sensor uses a single RJ45 shielded cable for the output signals.

Sensor Outputs:

The sensor provides a single 1ft RJ45 shielded cable for the output signals. The voltage range is from 0 to 5 Volts. It comes equipped with a pair of red and black binding posts for the monitored contact.

Sensor Specifications:

Voltage Range	0 to 5 Volts
Supply Voltage	5 VDC
Supply Current	1 Milliamps
Contact (Open)	0 Volts
Contact (Closed)	5 Volts
Dimensions (L x W x H)	3.37" x 2.12" x 1.50" Inches
Temperature Range	-40 to 85 °C
Humidity Range	0 to 90% Non-condensing
Cable Length	1 ft
Cable Connector Type	RJ45 Male

Contact Us:

To purchase sensors, please contact our Sales Department at 800-818-3463, sales@softstuf.com

Hours: Monday - Friday, 9:00 a.m. to 6:00 p.m. EST
(Visa, Master Card, American Express, & POs accepted)

Mailing Address:

SOFTSTUF, Inc.
P.O. Box 40245
Philadelphia, PA 19106-0245
www.softstuf.com

Support:

Phone: 800-818-3463
Fax: 609-677-8736
support@softstuf.com